

Datasheet - NDTGN

Command and signalling devices / Push buttons and pilot lights - "N" Program / NDT - Push button



(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	NDTGN
Article number	101163556
EAN code	4250116200030
eCl@ss	27-37-12-13

Approval

Approval



USA/CAN



BG

Global Properties

Product name	NDT - Push button
Standards	IEC/EN 60947-1, EN 60947-5-1
Compliance with the Directives (Y/N)	No
Suitable for safety functions (Y/N)	No
Mounting	mounting flange EFM
Materials	
- Material of the operators	ABS
- Material of the front ring	ABS, Chromium-plated
Design	Embeddable button - Front plate mounting
Form	Round
Color	

- Colour of the operating element	 green
- Colour of the bellows	 White
- Colour of the front ring	 Silver
Weight	25 g
Manner of using	
Can be illuminated (Y/N)	No

Mechanical data

Actuating stroke	5 mm
Latching (Y/N)	No
Unlocking type	without
Probing possible (Y/N)	Yes
mounting flange available (Y/N)	Yes
Front plate thickness	
- min. front plate thickness	1.5 mm
- max. front plate thickness	6 mm
Tightening torque for fixing screws	0,6 Nm

Ambient conditions

Ambient temperature	
- Min. environmental temperature	-25 °C
- Max. environmental temperature	+80 °C
Storage and transport temperature	
- Min. Storage and transport temperature	-
- Max. Storage and transport temperature	-
Fully insulated (Y/N)	Yes
Sealing type	membrane, lip seal
Protection type IP	IP67, IP69K

LED switching conditions display

With integrated LED (Y/N)	No
---------------------------	----

Dimensions

Dimensions	
- Height	11 mm
- diameters for the actuating heads	Ø 44.5 mm
- Hole, diameter	22.3 mm + 0,4 mm
Spacing	50 x 50 mm

Documents

Declaration of conformity (de) 93 kB, 30.06.2014

Code: __n-pp01_de

Declaration of conformity (en) 81 kB, 22.08.2014

Code: __n-pp01_en

BG-test certificate (de, en, fr) 174 kB, 31.07.2014

Code: z_ndrp01


IPA Data (en) 248 kB, 09.11.2012

Code: i_ipap02

IPA Data (de) 255 kB, 09.11.2012

Code: i_ipap01

Images



Application

System components

Accessories



101014388 - EFM



NSK - Protective collar against unintentional contact

- for pushbuttons and illuminated pushbuttons

contact element



contact element EF - (N)

- Flat plug-in connector
- Mounting flange position 2
- 21-22 (Contact labelling)

The data and values have been checked thoroughly. Technical modifications and errors excepted.
Generiert am 18.01.2016 - 21:35:28h Kasbase 3.2.1.F.64I