

## Datasheet - BNS 16-12ZD

Safety sensors / BNS 16



Preferred typ



- Thermoplastic enclosure
- Suitable for food processing industry
- Concealed mounting possible
- 52 mm x 90 mm x 32 mm
- Long life
- no mechanical wear
- Insensitive to transverse misalignment
- Insensitive to soiling
- 3 cable entries M 20 x 1.5
- Wiring compartment

(Minor differences between the printed image and the original product may exist!)

### Ordering details

Product type description	BNS 16-12ZD
Article number	101172563
EAN code	4030661301167
eCl@ss	27-27-24-02

### Approval


Approval



### Classification

Standards	EN ISO 13849-1
B <sub>10d</sub> Opener/Normally open contact (NC/NO)	25.000.000
- notice	at max. 20% contact load
Mission time	20 Years
notice	$MTTF_d = \frac{B_{10d}}{0,1 \times n_{op}}$ $n_{op} = \frac{d_{op} \times h_{op} \times 3600 \text{ s/h}}{t_{cycle}}$

### Global Properties

Product name	BNS 16
Standards	IEC 60947-5-3, BG-GS-ET-14
Compliance with the Directives (Y/N) 	Yes
Materials	
- Material of the housings	Plastic, glass-fibre reinforced thermoplastic
Weight	150 g
Coding available (Y/N)	Yes
Monitoring function of downstream devices (Y/N)	No
Prerequisite evaluation unit	Yes
Recommended safety-monitoring module	AES 1135, AES 1136, AES 1165, AES 1166, AES 1165-2250, AES 1185, AES 1235, AES 1236, AES 1265, AES 1266, AES 1337, AES 2135, AES 2136, AES 2335, AES 2336, AES 2535, AES 2536, AES 2365, AES 2366, AES 2565, AES 2566, AES 2285, AES 3075, SRB 202C., SRB 400C.
Recommended actuator	BPS 16

## Mechanical data

Design of electrical connection	Screw connection
Cable section	
- Min. Cable section	0,25 mm <sup>2</sup>
- Max. Cable section	1.5 mm <sup>2</sup>
AWG-Number	15
mechanical installation conditions	not flush
Active area	cover-side
Ensured switch distance ON	8 mm
Ensured switch distance OFF	18 mm
notice	All indications about the cable section are including the conductor ferrules.
Type of actuation	Magnet
Direction of motion	head-on with regard to the active surface
restistance to shock	30 g / 11 ms
Resistance to vibration	10 ... 55 Hz, Amplitude 1 mm

## Ambient conditions

Ambient temperature	
- Min. environmental temperature	-25 °C
- Max. environmental temperature	+70 °C
Storage and transport temperature	
- Min. Storage and transport temperature	-25 °C
- Max. Storage and transport temperature	+70 °C
Protection class	IP67

## Electrical data

Integrated Safety monitoring module available (Y/N)	No
Cross circuit/short circuit recognition possible (Y/N)	Yes
Voltage type	VAC/DC
Switch frequency	max. 5 Hz
Switching voltage	max. 100 VAC/DC
Switching current	max. 400 mA
Switching capacity	max. 10 W

## Outputs

Design of control output	Other, Reed kontakts
Number of shutters	1 piece
Number of openers	2 piece

### Electrical data - Safety outputs

Number of secure semi-conductor outputs	0 piece
Number of secure outputs with contact	0 piece

### Electrical data - Diagnostic output

Number of semi-conductor outputs with signaling function	0 piece
Number of outputs with signaling function that already have a contact	0 piece

### LED switching conditions display

LED switching conditions display (Y/N)	No
--	----

### ATEX

Explosion protection categories for gases	None
Explosion protected category for dusts	None

### Dimensions

Dimensions of the sensor	
- Width of sensor	52 mm
- Height of sensor	90 mm
- Length of sensor	39 mm

### notice

Contact symbols shown for the closed condition of the guard device.


### Included in delivery

Actuators must be ordered separately.


### Indication legend

5 different directions of actuation: cover, front and below, right and left


### Diagram



Note Diagram

 positive break NC contact

 active



- Normally-open contact
- Normally-closed contact

## Ordering code

---

BNS 16-(1)Z(2)-(3)

(1)

- 11 1 Normally open contact (NO) / 1 Opener (NC) (Only for Plug-in connection)
- 12 1 Normally open contact (NO) / 2 Opener (NC)

(2)

- V Actuating planes front side
- R Actuating planes right-hand side
- L Actuating planes left-hand side
- D Actuating planes cover-side
- U Actuating planes bottom
- LR Actuating planes left-hand side/right-hand side

(3)

- ST1 Connector Middle
- ST2 Connector right
- ST3 Connector left

## Documents

---

**Operating instructions and Declaration of conformity (es)** 309 kB, 09.10.2013

Code: mrl\_bns16\_es

**Operating instructions and Declaration of conformity (pl)** 320 kB, 20.11.2013

Code: mrl\_bns16\_pl

**Operating instructions and Declaration of conformity (da)** 313 kB, 15.10.2015

Code: mrl\_bns16\_da

**Operating instructions and Declaration of conformity (de)** 326 kB, 11.01.2016

Code: mrl\_bns16\_de

**Operating instructions and Declaration of conformity (en)** 321 kB, 11.01.2016

Code: mrl\_bns16\_en

**Operating instructions and Declaration of conformity (nl)** 315 kB, 14.02.2014

Code: mrl\_bns16\_nl

**Operating instructions and Declaration of conformity (jp)** 414 kB, 09.10.2013

Code: mrl\_bns16\_jp

**Operating instructions and Declaration of conformity (cs)** 308 kB, 02.03.2012

Code: mrl\_bns16\_cs

**Operating instructions and Declaration of conformity (it)** 306 kB, 09.10.2013

Code: mrl\_bns16\_it

**Operating instructions and Declaration of conformity (ro)** 308 kB, 24.01.2012

Code: mrl\_bns16\_ro





Operating principle

---

## System components

---

### Actuator

101172566 - BPS 16

