



The right label for virtually every situation and surface.



Indoor/Outdoor Vinyl

For general labelling or extreme conditions. Vinyl labels offer moisture, chemical and UV resistance, making them ideal for labelling both indoors and outdoors. Available in the widest range of colours that adhere to OSHA, ANSI and ISO colour standards.

UL recognised as a component to UL 969

Flexible Nylon

For labelling wires, cables and rounded surfaces. Flexible Nylon labels conform and stick tightly to wires, cables, curved and textured surfaces. Tear-proof material resists damage when pulled through tight spaces or conduits.

UL recognised as a component to UL 969

Permanent Polyester

For labelling panels, blocks, faceplates, shelves, bins, beams and more. Permanent Polyester labels have a polished finish that leaves your work looking professional. Available in smaller widths that fit most patch panels, blocks and other distribution panels.

UL recognised as a component to UL 969

Heat-Shrink Tube

For high-end cable identification. A 3:1 shrink ratio helps ensure a secure fit on wires and cables. Print directly on Heat-Shrink Tubes with any DYMO Industrial labelling tool.

Meets MIL-M-81531, MIL-STD-202G, SAE-DTL- 23053/5 (Class 1 & 3)
UL recognised as a component to UL 224

Self-Laminating

Self-Laminating labels protect your printed area from exposure to oil, solvents, water and abrasion when applied to wires and cables.

All DYMO Industrial labels are RoHS compliant.

For technical specifications on all DYMO Industrial label types, please visit our website at:
www.dymo.com






How to choose the right DYMO Industrial label:

	ENVIRONMENT	Heat/Cold Resistant	UV Light Resistant	Oil Resistant	Water Resistant	Chemical Resistant	Colour Coding
SURFACE							
Cable/Wire		Flexible Nylon Heat-Shrink Tube	Indoor/Outdoor Vinyl Heat-Shrink Tube	Indoor/Outdoor Vinyl Heat-Shrink Tube	Indoor/Outdoor Vinyl Heat-Shrink Tube	Indoor/Outdoor Vinyl Heat-Shrink Tube	Indoor/Outdoor Vinyl
Curved Surface		Flexible Nylon Indoor/Outdoor Vinyl	Indoor/Outdoor Vinyl Flexible Nylon	Indoor/Outdoor Vinyl	Indoor/Outdoor Vinyl Flexible Nylon	Indoor/Outdoor Vinyl	Indoor/Outdoor Vinyl
Flat Surface		Permanent Polyester Flexible Nylon	Permanent Polyester Indoor/Outdoor Vinyl	Permanent Polyester Indoor/Outdoor Vinyl	Permanent Polyester Indoor/Outdoor Vinyl	Permanent Polyester Indoor/Outdoor Vinyl	Indoor/Outdoor Vinyl
Textured Surface		Permanent Polyester Flexible Nylon	Indoor/Outdoor Vinyl Permanent Polyester	Indoor/Outdoor Vinyl Permanent Polyester	Indoor/Outdoor Vinyl Permanent Polyester	Indoor/Outdoor Vinyl Permanent Polyester	Indoor/Outdoor Vinyl

Top – Best Option Bottom – Alternate Option

Available DYMO® Industrial label widths and colours:



IND	LABEL APPLICATIONS	LABEL COLOUR	6mm	9mm	12mm	19mm	24mm
	Labels that stick and stay stuck. DYMO Industrial labels are tough— jobsite tested and UL recognised. Labels won't smear or fade and are built with industrial-strength adhesives to resist moisture, UV light and extreme temperatures. Whether you are labeling to OSHA, ISO and ANSI colour standards or labeling in harsh conditions, DYMO Industrial labels have you covered. DYMO Industrial labels are designed to work with Rhino and LabelManager printers and to perform on a variety of surfaces. LEARN MORE: www.dymo.com.au	BLACK ON WHITE	-	8D18443	8D18444	8D18445	-
		WHITE ON BLACK	-	1805437	1805435	1805436	1805432
	VINYL Length 5.5m - UL Recognised Component to UL969 - RoHS compliant 						
	PERMANENT POLYESTER Length 5.5m - UL Recognised Component to UL969 - RoHS compliant 	BLACK ON WHITE	1805442	8D18482	8D18483	8D18484	8D1734523
		BLACK ON CLEAR	1805440	18508DMO	622289	622290	1805433
		BLACK ON METALLIC	-	18485	18486	18487	1805434
	HEAT-SHRINK TUBE Length 1.5m - UL Recognised Component to UL224 - Meets MIL-STD-202G, MIL-M-81531 & SAE-DTL 23053/5 (Class 1 & 3) - RoHS compliant 	BLACK ON WHITE	8D18051	8D18053	8D18055	8D18057	-
		BLACK ON YELLOW	18052	18054	18056	18058	-
	FLEXIBLE NYLON Length 3.5m - UL Recognised Component to UL969 - RoHS compliant 	BLACK ON WHITE	-	-	8D18488	8D18489	8D1734524
		BLACK ON YELLOW	-	-	8D18490	8D18491	8D1734525
	SELF-LAMINATING Length 5.5m - RoHS compliant 	BLACK ON WHITE	-	-	-	-	8D1734821

www.dymo.com.au