

FX/TM2

Electronic thermostats with digital display



Characteristics

- Current rating 10 A.
- Power supply from 200 to 250 V.
- Accuracy +/- 1% of temperature range.
- Dimensions 87 x 53 x 58 mm.
- Temperature display +/- 1°C.
- Adjustable differential.
- The sensor can be extended and positioned 50 m away from the thermostat.

Thermostat **FX/TM2/120**

- Temperature range : from - 30°C to + 120°C.
- CTN sensor 10 000 ohms at 25°C.
- Sensor length : 3 m.

Thermostat **FX/TM2/200**

- Temperature range: from - 30°C to + 200°C.
- Sensor with 3 wires PT 100 ohms at 0°C.
- Sensor length : 3 m.

Applications

The **FX/TM2** range of electronic thermostats is used for accurate temperature control.

To keep piping and its contents at the right temperature, a control device provides the following advantages :

- the heating element is energised only when necessary.
- the heating element lifetime is increased.
- the heating element will not overheat.
- the energy consumed is kept to a minimum.

The **FX/TM2** thermostat is fitted to a DIN rail in an electrical cabinet.

FX/BOITIER option

The thermostat can be fitted in an IP 54 box (195 x 115 x 110 mm).

Electrical connection diagram



FX/TM2/120



FX/BOITIER



FX/TM2/200



Use

Consult the pages of the catalogue devoted to the corresponding general operating principles, general instructions for use and accessories.

FLEXELEC S.A.S

10, rue des frères Lumière
Z.A. du Bois Rond
69720 ST BONNET DE MURE - FRANCE
Tel.: + 33 (0)4.72.48.30.90
Fax: + 33 (0)4.78.40.82.81
E-mail: flexelec@omerin.com

FLEXELEC Dept

OMERIN ASIA Pte Ltd
51 Goldhill Plaza #08-11
SINGAPORE 308900
Tel.: + 65 6255 4778
Fax: + 65 6255 4779
E-mail: sales@omerin.com.sg

FLEXELEC (UK) Ltd

Unit 11 Kings Park Industrial Estate
Primrose Hill - KINGS LANGLEY
Hertfordshire - WD4 8ST - UK
Tel.: + 44 (0) 1923.274477
Fax: + 44 (0) 1923.270264
E-mail: sales@omerin.co.uk

FLEXELEC Dept

OMERIN GmbH
Buchwiese 16
D-65510 IDSTEIN - GERMANY
Tel.: + 49 (0) 6126.94.31-0
Fax: + 49 (0) 6126.83.99
E-mail: omeringmbh@omerin.com