



BUNKER 15 ROUND SENSOR SL7272 - 15W

LED 15 watt surface mount round shaped bunker, IP54 with PIR sensor

Application

A robust solution for residential and apartment interior or exterior covered eave utility spaces

Design Specifications

- Durable UV resistant white or black polycarbonate body, opal polycarbonate diffuser
- Integral control gear, 15 watt with PIR sensor control, fixed 30 seconds ON
- Max. 7 metres detection distance
- CRI > 80, 1050lm
- Quick connect installation design
- Robust IK08 protection



Technical Specification


Model No.	Description	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
SL7272CW/WH/S	LED BUNKER 15W ROUND IP54 4K WH SENSOR	240	15	1050	4000	80
SL7272CW/BK/S	LED BUNKER 15W ROUND IP54 4K BK SENSOR	240	15	1050	4000	80

Technical Specification

Model No.	Beam Angle (°)	Body Colour	Dim (mm)
SL7272CW/WH/S	110	WHITE	182(W) x 68(H)
SL7272CW/BK/S	110	BLACK	182(W) x 68(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".


Dimensions



Photometric Data

Unit: cd C0/C180 _____ C90/C270 _____

SL7272CW/WH/S at 4000K





Product Images

