



## BUNKER 15 ROUND SL7272 - 15W

LED 15 watt surface mount round shaped bunker, IP65

### Application

A robust solution for residential and apartment interior or exterior covered eave utility spaces

### Design Specifications

- Durable UV resistant white or black polycarbonate body, opal polycarbonate diffuser
- Integral control gear, 15 watt.
- CRI > 80, 1050lm
- Quick connect installation design
- Robust IK08 protection



### Technical Specification


Model No.	Description	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
SL7272CW/WH	LED BUNKER 15W ROUND IP65 4K WH	240	15	1050	4000	80
SL7272CW/BK	LED BUNKER 15W ROUND IP65 4K BK	240	15	1050	4000	80

### Technical Specification

Model No.	Beam Angle (°)	Body Colour	Dim (mm)
SL7272CW/WH	110	WHITE	182(W) x 68(H)
SL7272CW/BK	110	BLACK	182(W) x 68(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".


## Dimensions



## Photometric Data

Unit: cd C0/C180 \_\_\_\_\_ C90/C270 \_\_\_\_\_

### SL7272CW/WH at 4000K





## Product Images

---

