



NEW BONDI II SL7224 - 11W

IP65 LED (UP/DOWN) architectural wall luminaire

Application

A decorative residential exterior or interior solution

Design Specifications

- Aluminium body profile, powder coat black or silver finish
- Clear tempered glass cover
- Polycarbonate optical lens
- High efficiency SMD LED chips
- Integral constant current non-dimmable LED driver
- Up and down light distribution



Technical Specification

Model No.	Description	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
SL7224WW/BK	LED WALL LIGHT 11W IP65 3K BK	240	11	800	3000	80
SL7224WW/SL	LED WALL LIGHT 11W IP65 3K SL	240	11	800	3000	80

Technical Specification

Model No.	Beam Angle (°)	Dim (mm)	Body Colour
SL7224WW/BK	38	104(W) x 187(H)	BLACK
SL7224WW/SL	38	104(W) x 187(H)	SILVER

* Lumens and Power shown are TOTAL luminaire lumens (lm) and power (W).

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

SL7224

