



PLUTO 100

Australian approved constant voltage LED driver IP67

Application

An ideal choice for LED strips, LED Neon or exterior lighting requirements

Design Specifications

- SELV and EMC compliant
- Safe no load operation, power factor 0.95
- Overload and short circuit protection
- 1.2m flex and plug fitted for easy installation, output (secondary) end is provided with rubber fly leads
- Durable metal casing IP67
- Minimum load 10 watt




Technical Specification

Model No.	Description	Input Voltage (V/AC)	Output Voltage (V/DC)	Power (W)	Power Factor	Dim (mm)
PLUTO 100/12V	LED DRIVER 12V 100W C-VOLTAGE	240	12	100	0.9	262(L) x 40(W) x 23(H)
PLUTO 100/24V	LED DRIVER 24V 100W C-VOLTAGE	240	24	100	0.9	262(L) x 40(W) x 23(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Dimensions



Wiring Diagram

