



## PLUTO 200

Australian approved constant voltage LED drivers IP66

### Application

An ideal choice for LED strips, LED Neon or inground lighting requirements

### Design Specifications

- SELV and EMC compliant
- Safe no load operation, power factor 0.95
- Overload and short circuit protection
- 1.2 m flex and plug fitted for easy installation, output (secondary) end is provided with rubber fly leads
- Durable metal casing IP66
- Minimum load 10 watt



### Technical Specification

Model No.	Description	Input Voltage (V/AC)	Output Voltage (V/DC)	Power (W)	Power Factor	Dim (mm)
PLUTO 200/12V	LED C/VOLTAGE DRIVER	240	12	200	0.95	252(L) x 68(W) x 39(H)
PLUTO 200/24V	LED C/VOLTAGE DRIVER	240	24	200	0.95	252(L) x 68(W) x 39(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

## Dimensions

### Wiring Diagram

